

专注APT攻击与防御

<https://micropoor.blogspot.com/>

1.是否开启远程桌面，1表示关闭，0表示开启

```
EXEC master..xp_RegRead 'HKEY_LOCAL_MACHINE','SYSTEM\CurrentControlSet\Control\Terminal Server','fDenyTSConnections'
```

Value	Data
1 fDenyTSConnections	0

2.读取远程桌面端口

```
EXEC master..xp_RegRead 'HKEY_LOCAL_MACHINE','SYSTEM\CurrentControlSet\Control\Terminal Server\WinStations\RDP-Tcp','PortNumber'
```

Value	Data
1 PortNumber	3389

3.开启远程桌面

```
EXEC master.dbo.xp_RegWrite 'HKEY_LOCAL_MACHINE','SYSTEM\CurrentControlSet\Control\Terminal Server','fDenyTSConnections','REG_DWORD',0;
```

reg文件开启远程桌面：

```
Windows Registry Editor Version 5.00
[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Terminal Server]
"fDenyTSConnections"=dword:00000000
[HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Terminal Server\WinStations\RDP-Tcp]
"PortNumber"=dword:00000d3d
```

////

保存micropoor.reg，并执行regedit /s micropoor.reg

注：如果第一次开启远程桌面，部分需要配置防火墙规则允许远程端口。

```
netsh advfirewall firewall add rule name="Remote Desktop" protocol=TCP dir=in localport=3389 action=allow
```

4.关闭远程桌面

```
EXEC master.dbo.xp_regwrite'HKEY_LOCAL_MACHINE','SYSTEM\CurrentControlSet\Control\Terminal  
Server','fDenyTSConnections','REG_DWORD',1;
```

- Micropoor